

TYPICAL CHARACTERISTICS:

Appearance	Clear colourless liquid
Physical State	Liquid
Flash Point	> 100°C
Boiling Point	98°C
Freezing Point	0°C
Specific Gravity	1.01 – 1.04
pH	10.1– 11.4
Odour	No added odour
Density	8.34 – 8.67 lb/gal
Solubility	100%

Safety Data Sheet Available at: SimpleGreen.com.au

TYPICAL USES: Hard non-porous surfaces, parts washers, pressure washers, etc. Can be applied with a pressure washer, high or low volume foamer, low pressure sprayer or trigger applicator. Can be used in a floor scrubber, mop bucket, parts washer and ultrasonic bath. **See label for additional uses.**

SAFETY: No special PPE requirements for handling. Safe work practices are recommended such as the use of safety glasses, goggles or shields. PVC or nitrile gloves are suggested for individuals prone to dry skin.



SIMPLE GREEN® MINE CLEAN HEAVY-DUTY CLEANER & DEGREASER

A concentrated, cleaning and degreasing agent
A clear liquid with no added fragrance

UNIQUE FEATURES

- Not classified as hazardous according to Model Work Health & Safety Regulations and GHS Criteria
- No special PPE requirements for handling (safe work practices are recommended)
- Not classified as hazardous for transport
- Low foaming so less water is required when rinsing
- Features Quick Break making it ideal to use in facilities equipped with an oil/water separator for waste disposal
- Readily biodegradable, non-abrasive, non-corrosive, non-flammable and rinses residue-free
- Concentrated formula made in Australia
- The safer alternative to dangerous, flammable, caustic degreasers and solvents

APPLICATIONS

- Vehicle washdown, machinery, work tools, plant & equipment, engines, traction motors, railway carriages, crushers & conveyors, rubber screens, etc.
- Janitorial cleaning, shut down cleaning, workshops, site offices, site accommodation, floors, walls, stairways, windows & mirrors, kitchen & dining, etc.
- Formulated to remove petroleum greases, coolants, transmission & radiator fluids, greasy soils, oil, dirt, brake dust, road grime & stains, graphite, bitumen, metal working fluids, mud & clay, tree sap, bug & bird droppings.
- Safe to use on bare and painted metals, stainless steel, aluminium, chrome, copper, brass, seals, rubber, canvas, carpets, drains, gaskets, glass, acrylic, plastics, stone (natural & synthetic) and more.

DIRECTIONS FOR USE

Use the recommended dilution ratios below as a guide and agitate with a brush or sponge if required. Rinse or pressure wash off to leave a residue-free finish.

- **Light cleaning:** Mix 5% concentrate with 95% water. Dusts, particulates, very light oils.
- **Medium cleaning:** Mix 20% concentrate with 80% water. Greases & oils, most metal working fluids, hydraulic fluids, dirt, grime, food residue.
- **Heavy cleaning:** Mix 50/50 or use at full strength. Thick grease, oil, carbons & soot, baked-on soils, tough soils lodged in porous surfaces.
- **Parts Washers:** Mix 25% concentrate with 75% water.
- **Pressure Washers:** Mix 5% concentrate with 95% water.
- **Ultrasonic Baths:** Mix 50% concentrate with 50% water.

PART#	SIZE	UNITS	CASE WEIGHT	CASE DIMENSIONS (CM)	ITEM UPC
SG20020	20 L	1	21.5 kg	27 x 27 x 38	0-43318-00050-8
SG20208	208 L	1	222 kg	58.92 x 58.92 x 88.52	0-43318-00051-5
SG21041	1040 L	1	1127 kg	121.9 x 101.6 x 116.8	0-43318-00052-2

