



SIMPLE GREEN® Hi-Flow Single Dilution Proportioner

Ideally suited for filling pressure washers, scrubbers etc.

UNIQUE FEATURES

- Represents the most intuitive and cost effective dispensing system available in the market today
- By combining revolutionary technology of patented hydrodynamics and user friendly, image enhancing features, the Simple Green Hi-Flow Single Dilution Proportioner provides the perfect solution for all institutional and light industrial chemical dilution applications
- Watermark approved backflow device to avoid chemical contamination of the inlet water
- Flow rate of 14 litres per minute
- Working pressure from 1 bar
- Working temperature up to 70 C
- Inlet connection is 3/4" BSP and is compatible with all Australian fittings
- Metering tips are inserted from the outside speeding up installation time
- Solenoid valve type magnet activation
- Robust and durable PP enclosure

INCLUDES

- Standard Metering tips
- Bucket fill hose
- 1.5m easy hooker water hose
- 3/4 x 1/2" Brass inlet fitting
- 20mm x 15mm BSP brass adaptor



OPTIONAL

- Ultra metering tips are available for purchase separately

	Tip Color	Diameter (mm)	Ratio	%
	No Tip	-	5:1	18
STANDARD METERING TIP	Grey	3.250	6:1	17
	Black	2.540	7:1	16
	Biege	1.780	9:1	12
	Red	1.320	13:1	7
	White	1.090	20:1	5
	Blue	1.010	23:1	4
	Tan	0.880	31:1	3
	Green	0.710	53:1	2.5
	Orange	0.630	69:1	2
	Brown	0.580	80:1	1.5
	Yellow	0.510	96:1	1
	Aqua	0.460	121:1	0.8
	Purple	0.360	217:1	0.5
	Pink	0.250	400:1	0.3
ULTRALEAN TIP	Lime	0.228	476:1	0.21
	Burgundy	0.208	625:1	0.16
	Pumpkin	0.168	833:1	0.12
	Copper	0.155	1250:1	0.08

PART#	SIZE	UNITS	CASE WEIGHT	CASE DIMENSIONS (CM)	ITEM UPC
SG13887	TBA	1	TBA	TBA	N/A