

TYPICAL CHARACTERISTICS:

| | |
|------------------------|-------------------------|
| Appearance | Clear colourless liquid |
| Physical State | Liquid |
| Flash Point | > 100°C |
| Boiling Point | 98°C |
| Freezing Point | 0°C |
| Specific Gravity | 1.01 – 1.04 |
| pH | 10.1 – 11.4 |
| Odour | No added odour |
| Density | 8.34 – 8.67 lb/gal |
| Solubility | 100% |

Safety Data Sheet Available at: SimpleGreen.com.au

TYPICAL USES: Cleaning and degreasing agent that can be used full strength or diluted out. It replaces most cleaners, detergents, degreasers and solvents you're using now. **See label for additional uses.**

SAFETY: No special PPE requirements for handling. Safe work practices are recommended such as the use of safety glasses, goggles or shields. PVC or nitrile gloves are suggested for individuals prone to dry skin.



SIMPLE GREEN® SUPREME HIGH PERFORMANCE CLEANER AND DEGREASER

A concentrated, water-based cleaner/degreaser. A clear translucent liquid with no added colour or fragrance

UNIQUE FEATURES

- Not classified as hazardous according to Model Work Health & Safety Regulations and GHS Criteria
- No special PPE requirements for handling (safe work practices are recommended)
- Not classified as hazardous for transport
- Versatile formula cleans and degreases all washable surfaces
- Economical concentrated formula provides a more cost-effective solution for cleaning and degreasing
- Safer alternative to hazardous and caustic chemicals and solvents
- Readily biodegradable, non-corrosive, non-ionic, non-flammable, non-explosive, and non-abrasive
- No bleach, no ammonia, no petroleum solvents
- VOC compliant, contains no Clean Air Act Hazardous Air Pollutants (HAPs)
- Low foaming so less water is required when rinsing
- Replaces ozone depleting substances (ODS)
- Features Quick Break making it ideal to use in facilities equipped with an oil/water separator for waste disposal
- No added colour or fragrance
- Made In Australia

APPLICATIONS

- Floor scrubbing and general plant maintenance
- Engines, machinery, manufacturing equipment
- Dip tanks, aqueous-based parts washers, steam cleaners and pressure sprayers
- Food processing plants and food preparation areas (grills, vents, traps & more)
- Prepping prior to painting, plating or welding
- Fleet and mass transit vehicles
- HVACR coils and cooling towers
- Removing machining oils and cutting fluids from manufactured parts and extruded tubing

DIRECTIONS FOR USE

Can be applied with a pressure washer, high or low volume foamer, low pressure sprayer or trigger applicator. It can also be used in a floor scrubber, mop bucket, aqueous parts washer and ultrasonic baths. Use the recommended dilution ratios below as a guide and agitate with a brush or sponge if required. Rinse or pressure wash off to leave a residue-free finish.

- **Light cleaning:** Mix 5% concentrate with 95% water. Dusts, particulates, very light oils.
- **Medium cleaning:** Mix 20% concentrate with 80% water. Greases & oils, most metal working fluids, hydraulic fluids, dirt, grime, food residue.
- **Heavy cleaning:** Mix 50/50 or use at full strength. Thick grease, oil, carbons & soot, baked-on soils, tough soils lodged in porous surfaces.
- **Parts Washers:** Mix 25% concentrate with 75% water.
- **Pressure Washers:** Mix 5% concentrate with 95% water.
- **Ultrasonic Baths:** Mix 50% concentrate with 50% water.

| PART# | SIZE | UNITS | CASE WEIGHT | CASE DIMENSIONS (CM) | ITEM UPC |
|---------|--------|-------|-------------|-----------------------|-----------------|
| SG13492 | 20 L | 1 | 21.5 kg | 27 x 27 x 38 | 9-343318-134922 |
| SG13493 | 208 L | 1 | 222 kg | 58.92 x 58.92 x 88.52 | 9-343318-134939 |
| SG13494 | 1040 L | 1 | 1127 kg | 121.9 x 101.6 x 116.8 | 9-343318-134946 |

